

# INDUSTRIAL AIR COMPRESSORS



NT-1080V



NT-10120H

**Standard Features:**

- ✓ V-4 cylinder cast iron pump
- ✓ Low RPM for longer life
- ✓ Oil sight glass for rapid level checks
- ✓ Oil drain extension for easy oil changes
- ✓ Tapered roller bearings
- ✓ Ten individual concentric stainless steel disk valves
- ✓ Industrial motor, low speed
- ✓ Magnetic motor starter, mounted and wired, for all popular voltages.
- ✓ **Powder coated reservoir** for a brilliant and durable finish
- ✓ Factory tested, shipped with proper oil level and **READY TO WORK!**

Options available:
WV-1: Automatic drain (installed)
M-20: Air cooled aftercooler

Voltages available : 230/1 phase, 208-230-460/3 phase, 575/3 phase

**230 volts, single phase available**

SPECIFICATIONS										
Model Number	HP	Gal.	Pump	Cyl.	RPM	CFM @150	Dimensions (inches)			Weight (lbs)
							L	W	H	
NT-1080V	10	80	NT-10C	V-4	794	34	41	24	68	740
NT-1080H	10	80	NT-10C	V-4	794	34	63	20	44	760
NT-10120H	10	120	NT-10C	V-4	794	34	68	24	46	885

Due to continuing product improvement, specifications and features are subject to change. Pump warranted for 5 full years.